

Bulkheads & Syphon Tubes

PART NUMBER	DESCRIPTION	HOLE SIZE
10897	1/4" BRASS BULKHEAD	25/32"
10058	1/2" ACE BULKHEAD	1 1/4"
10025	1/2" POLYPROPYLENE BULKHEAD	1 3/8"
13208	3/4" ACE BULKHEAD	1 7/16"
10484	3/4" ACE HEAVY-DUTY BULKHEAD	1 3/4"
10485	1" ACE BULKHEAD	1 3/4"
10503	1" POLYPROPYLENE BULKHEAD	2 1/4"
10918	1-1/4" ACE BULKHEAD	2 1/4"
10507	1-1/2" ACE BULKHEAD	3"
10508	2" ACE BULKHEAD	3"
10486	2" STAINLESS STEEL BULKHEAD DOUBLE THREADED	3"
10912	2" ACE HEAVY-DUTY BULKHEAD FOR TANKS OVER 3000 GAL	3 1/4"
10490	2" SS BULKHEAD HEAVY FOR TANKS OVER 3000 GAL	3 1/4"
12528	3" ACE BULKHEAD	4 1/2"
10487	3" STAINLESS STEEL BULKHEAD DOUBLE THREADED	4 1/2"
11099	4" STAINLESS STEEL BULKHEAD	4 7/8"
10511	2" SYPHON TUBE	
10488	2" LONG SYPHON TUBE	
10489	3" LONG SYPHON TUBE	
13470	4" LONG SYPHON TUBE	

FEATURES

- Retainer ring molded into each fitting prevents the sealing gasket from expanding or sliding out of position under compression
- Bearing washer insures even compression on the gasket and promotes sealing
- Each fitting features left hand compression threads to prevent loosening while installing mating fittings
- Internal threads feature female pipe threads and are provided on both sides of the fitting. Mating fittings can be installed on both sides of the installed fitting
- Sealing gaskets are produced from Santoprene Thermoplastic Rubber (TPR)
- Fitting compression nuts feature a specially designed cross-section to prevent distortion under load

